Connectors to Relay Board 11117844A

CL1	CL2	QTY	NUMBER	CHANGE	DD.MM.YY	DRAW	CHECK

BASIC CONTROL PANEL

11116024A

6 5 4 3 2 1
12 11 10 9 8 7

PART# 550209A

1 2 3 4 5 6
7 8 9 10 11 12

18 Orange	11	11	20 Orange
18 Brown	8	8	20 Brown
18 Purple	3	3	20 Purple
18 Red	12	12	20 Red
18 Green with purple strip	5	5	20 Gray
18 Yellow	2	2	20 Yellow
18 Blue	4	4	20 Blue
18 Green	1	1	20 Green
18 Black with purple strip	7	7	20 Black

NC NC NC NC NC NC

Brown

BAT

SEE BATTERY CABLE NOTE BELOW

X1

7 4 1
8 5 2
9 6 3

PART# 550221A

X5

Connectors X5, X6, X7

2 4 6 8 / 1 3 5 7

PART# 550236A
6x-550311A
2x-550710A

MIN	1
MED	8
MAX	4
+30 BAT	3
MIN	2
MED	6
MAX	7
+30 BAT	5

RELAY
87 30
86 85

12 Gray	1
12 Orange	2
14 Light Blue	3
10 Red	4
12 White	5
12 Yellow	6
14 Dark Blue	7
10 Red	8

EVAPORATOR

IW 200
IW 210
IW 220
CE 200
CE 300

8 7 6 5 / 4 3 2 1

PART# 178764Z
4x-550178A
2x-550645A
2x-176591Z

5 6 7 8 / 1 2 3 4

ON UNIT

RELAY
87 30 +12V
86 85
OPTIONAL

CLUTCH

1	14 Gray	
2	14 White	

X4

2 1

PART# 178802Z
1x-176389Z

Reserved for 3rd blower Application or 2nd Evaporator

X6

MIN	1
MED	8
MAX	4
+30 BAT	3
MIN	2
MED	6
MAX	7
+30 BAT	5

1	
2	CE 300
3	3RD BLOWER
4	

RELAY
87 30
86 85

Dot-lines are reserved for 3rd blower

4 5 6 / 1 2 3

PART# 550262A

6 5 4 / 3 2 1

ON UNIT

X7

2	FAN 1	
1	FAN 2	
3	FAN 3	
8	GND 1	
7	GND 2	
6	GND 3	
NC		
NC		

2 4 6 8 / 1 3 5 7

PART# 550236A
3x-550710A

CONDENSER

SC 120
SC 220
SC 230
RC 320
RC 430

1	10 + Green	
2	10 + Green	
NC		
4	10 - Brown	
5	10 - Brown	
NC		

Dot-lines are reserved for 3 Fans Application

X8

3	14
6	14
5	14
4	14
1	14
NC	

4 5 6 / 1 2 3

PART# 550262A

*X8

3	
6	
5	
4	
1	
NC	

* Master/slave interface for single control dual loop system
PART# 550356A

Optional noise suppression relay

+30 (Battery)
+15 (Ignition)

14 Blue

X2

1 2

PART# 2710124A
2x-176591Z

D+(Alternator)

14 Purple

ACCUM.

L.P.S. Optional Location

COND.

High Pressure Switch

EVAP.

Low Pressure Switch

Ice Switch

1 3 S1 S2

1	1		
2	2		14 Black
3	3		14 White
4	4		14 Gray

Temperature Sensor

2 4 / 1 3

PART# 178748Z
4x-176591Z

X3

1 2

Red

BAT

100 AMP FUSE

Wire Gauge AWG	Maximum Wire Length @12 Volts DC 100 Amps
4	37 Ft.
2	60 Ft.
1	76 Ft.

Note: Maximum recommended wire lengths based on 1/2 volt maximum voltage drop.

REF./POS. DIM ( ) INFORMATION DIM ··· NOT SCALED DIM

PERMISSIBLE DEVIATION FOR DIM WITHOUT TOLERANCES	VOLTAGE	WEIGHT	CAD SYSTEM
ANSI	12		CATIA V5R19
MATERIAL			
SURFACE PROTECTION			

PART NAME
ARCTICSPHERE SPLIT SYSTEM WITH HIGH SPEED FAN RELAY'S

DATE	02/06/14	02/06/14	02/06/14	SCALE FREE	DOC NO.
NAME	RAYY	JIMW	JIMW		
	DRAW	CHECK	APP	STATUS	PART NO. 20000027B
SPHEROS				SIZE ISO A2	

REPLACED BY PART-NO. | REPLACEMENT FOR PART-NO. | PAGE 1 / 1

176380Z