

Premium EM-7

The premium EM-7 ceiling mount air-conditioning evaporator comes with the industry's most modern, efficient and high technology, such as transverse blower technology and long life


motors. Yet, it's still very easy to service and to install thanks to its smart design. The premium EM-7 is the lowest profile and lightweight evaporator on the market.



Features	Benefits
Transverse blower technology	Provides uniform air flow across the slanted coil which increases evaporator performance and efficiency.Lowest noise levels and maximum air throw
New extreme long life motors	Offers unparalleled 10,000 hours usage
Available for front and rear ceiling mount	Flexible to fit any application
Galvanized steel frame	Strength and durability
State of the art enhanced coil	Maximum capacity and efficiency
Attractive plastic cover available in two colors	

MCC • Dec 2015 PN: 89-3092

Premium EM-7 Evaporators



Technical Data

Cooling capacity	35000 Btu/hr (8.8 kW) IMACA [1]
	13700 Btu/hr (3.5 kW) ARI [2]
Max amperage requirement	16 A @ 13.5 V dc (High Speed) Voltage
Air flow	376 CFM (640 m³/hr) ^[3]
Refrigerant	R134a
Length	25.39 (645 mm)
Width	19.13 (486 mm)
Height	7.68 (195 mm)
Weight	39 lbs (17 kg)
Condensate drain connection	½ (12.7 mm) O.D (doal drains)
Cover color	Snow White or Dove Gray

- [1] IMACA conditions: 100°F (38°C) / 90°F (32°C) / 50% RH [2] ARI conditions:: 95°F (35°C) / 80°F (27°C) / 50% RH
- [3] Airflow is tested at super high speed with cover and louvers fully installed, O" static, 13.5 VDC

