

## Evaporator **IW-10**

The IW-10 unit frees up the overhead compartment where traditional evaporators are located. The IW-10 evaporator can also be matched with other MCC components to

provide a complete air conditioning system that meets your exact vehicle size, operating mode and climate.



### Features

- Lightweight aluminum construction
- Flexible mounting configurations
- Enhanced coils for maximum cooling capacity
- Easy access return air filter helps to reduce service time
- Flat or formed ABS cover
- Covers available in white or gray
- Flush mount installation provides maximum head clearance and clean OEM appearance



## Technical Data

Cooling capacity	55000 Btu/hr (16.1 kW) IMACA <sup>[1]</sup>	20580 Btu/hr (6.87 kW) ARI <sup>[2]</sup>
Air flow	1300 CFM (2208.7 m <sup>3</sup> )	
Refrigerant	R134a	
Length	43.30" (1100 mm)	
Width	7.00" (177.8 mm)	
Height	10.19" (259 mm)	
Weight	32 lbs (14.5 kg)	
Condensate drain connection	½" (12.7 mm) OD	
Max amperage requirement	23.7 A @ 13.5 V dc (High Speed)	
Voltage	12 or 24 VDC	
Cover color	Snow White or Dove Gray	

[1] IMACA conditions: 100°F (38°C) / 90°F (32°C) / 50% RH

[2] ARI conditions: 95°F (35°C) / 80°F (27°C) / 50% RH